

FORM PTO-590 (Modified)  
(Rev. 11-2000)

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

ATTORNEY'S DOCKET NUMBER

TRANSMITTAL LETTER TO THE UNITED STATES  
DESIGNATED/ELECTED OFFICE (DO/EO/US)  
CONCERNING A FILING UNDER 35 U.S.C. 371

204709US2PCT

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR

09/856179

INTERNATIONAL APPLICATION NO.  
PCT/JP00/04834

INTERNATIONAL FILING DATE  
19 July 2000

PRIORITY DATE CLAIMED  
12 January 2000

TITLE OF INVENTION

CALCULATION METHOD FOR PHYSICAL BODY DEFORMATION UNDER LOAD PROPAGATION

APPLICANT(S) FOR DO/EO/US

NISHI Yasukazu

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This is an express request to begin national examination procedures (35 U.S.C. 371(f)). The submission must include items (5), (6), (9) and (24) indicated below.
4. ☐ The US has been elected by the expiration of 19 months from the priority date (Article 31).
5. ☒ A copy of the International Application as filed (35 U.S.C. 371 (c) (2))
  - a. ☒ is attached hereto (required only if not communicated by the International Bureau).
  - b. ☐ has been communicated by the International Bureau.
  - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☒ An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)).
  - a. ☒ is attached hereto.
  - b. ☐ has been previously submitted under 35 U.S.C. 154(d)(4).
7. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371 (c)(3))
  - a. ☐ are attached hereto (required only if not communicated by the International Bureau).
  - b. ☐ have been communicated by the International Bureau.
  - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
  - d. ☒ have not been made and will not be made.
8. ☐ An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☐ An oath or declaration of the inventor(s) (35 U.S.C. 371 (c)(4)).
10. ☐ An English language translation of the annexes of the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5)).
11. ☐ A copy of the International Preliminary Examination Report (PCT/IPEA/409).
12. ☐ A copy of the International Search Report (PCT/ISA/210).

Items 13 to 20 below concern document(s) or information included:

13. ☐ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
14. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
15. ☒ A **FIRST** preliminary amendment.
16. ☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
17. ☐ A substitute specification.
18. ☐ A change of power of attorney and/or address letter.
19. ☐ A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825.
20. ☐ A second copy of the published international application under 35 U.S.C. 154(d)(4).
21. ☐ A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4).
22. ☐ Certificate of Mailing by Express Mail
23. ☒ Other items or information:

Notice for Consideration of Documents Cited in International Search Report/Notice of Priority/PCT/RO/101  
Drawings (11 Sheets)/PCT/RO/101 (English Translation)

U.S. APPLICATION NO. (IF KNOWN, PRE-37 CFR) <b>09/856179</b>		INTERNATIONAL APPLICATION NO. <b>PCT/JP00/04834</b>		ATTORNEY'S DOCKET NUMBER <b>204709US2PCT</b>	
---	--	--	--	---	--

24. The following fees are submitted:				<b>CALCULATIONS PTO USE ONLY</b>	
<b>BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)) :</b> <input type="checkbox"/> Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO ..... <b>\$1000.00</b> <input checked="" type="checkbox"/> International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO ..... <b>\$860.00</b> <input type="checkbox"/> International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO ..... <b>\$710.00</b> <input type="checkbox"/> International preliminary examination fee (37 CFR 1.482) paid to USPTO but all claims did not satisfy provisions of PCT Article 33(1)-(4) ..... <b>\$690.00</b> <input type="checkbox"/> International preliminary examination fee (37 CFR 1.482) paid to USPTO and all claims satisfied provisions of PCT Article 33(1)-(4) ..... <b>\$100.00</b>					
<b>ENTER APPROPRIATE BASIC FEE AMOUNT =</b>				<b>\$860.00</b>	
Surcharge of <b>\$130.00</b> for furnishing the oath or declaration later than months from the earliest claimed priority date (37 CFR 1.492 (e)). <input checked="" type="checkbox"/> 20 <input type="checkbox"/> 30				<b>\$130.00</b>	
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE		
Total claims	4 - 20 =	0	x \$18.00	<b>\$0.00</b>	
Independent claims	2 - 3 =	0	x \$80.00	<b>\$0.00</b>	
Multiple Dependent Claims (check if applicable). <input type="checkbox"/>				<b>\$0.00</b>	
<b>TOTAL OF ABOVE CALCULATIONS =</b>				<b>\$990.00</b>	
Applicant claims small entity status. (See 37 CFR 1.27). The fees indicated above are reduced by 1/2.				<b>\$0.00</b>	
<b>SUBTOTAL =</b>				<b>\$990.00</b>	
Processing fee of <b>\$130.00</b> for furnishing the English translation later than months from the earliest claimed priority date (37 CFR 1.492 (f)). <input type="checkbox"/> 20 <input type="checkbox"/> 30 +				<b>\$0.00</b>	
<b>TOTAL NATIONAL FEE =</b>				<b>\$990.00</b>	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31) (check if applicable). <input type="checkbox"/>				<b>\$0.00</b>	
<b>TOTAL FEES ENCLOSED =</b>				<b>\$990.00</b>	
				Amount to be: refunded	\$
				charged	\$

a. ☒ A check in the amount of **\$990.00** to cover the above fees is enclosed.


b. ☐ Please charge my Deposit Account No. \_\_\_\_\_ in the amount of \_\_\_\_\_ to cover the above fees. A duplicate copy of this sheet is enclosed.

c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. **15-0030**. A duplicate copy of this sheet is enclosed.

d. ☐ Fees are to be charged to a credit card. **WARNING:** Information on this form may become public. **Credit card information should not be included on this form.** Provide credit card information and authorization on PTO-2038.

**NOTE:** Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:



22850

Surinder Sachar  
Registration No. 34,423

\_\_\_\_\_  
SIGNATURE

**Marvin J. Spivak**  
NAME

**24,913**  
REGISTRATION NUMBER

*June 5 2001*  
DATE

11/19/85

09/856179

JC03 Rec'd PCT/4-TC 05 JUN 2001

# SPECIFICATION

Calculation method for physical body deformation under load propagation

## FIELD OF THE ART

The present invention relates to a calculation method for physical body deformation under load propagation for displaying a displacement of a total of a physical body by displaying movements of respective agents constituted by partitioning inside of the physical body into virtual predetermined shapes.

## BACKGROUND OF THE ART

In recent years, in the field of so-to-speak entertainment such as movie or commercial, CG ( Computer Graphics ) animation has frequently been used.

However, in order to reproduce deformation or motion of a physical body by CG, the main current is to make the deformation or motion by trial and error such that the deformation or motion looks just as it is or recovery from dynamic picture by a motion capture system constituting a big facility and alleviation of artificial load has yet to reach.

In order to know such a displacement of a structure ( object ) by external force, conventionally, there has been reduced into practice a Finite Element Method ( FEM ) for numerically solving differential equations for structural analysis ( which is not limited to a structure but nonstructural analysis of heat or fluid is included ) of the object, along with emergence of high-speed large-



obtain specialized knowledge of FEM to some degree.

According to stereoscopic picture display by the above-described computer graphics animation, one sheet of picture is represented by several tens thousands through several million of polygons, for example, in order to display an object physical body, it is necessary to calculate a plurality of polygons by operation to form the object physical body, operation of enormous matrices ( several tens thousands through several million for one picture ) is carried out at each time, further, environmental setting of color, light source or the like with regard to the picture is assumed by person and thereafter calculated by a computer or the like, further, the calculation must be carried out for a plurality of pictures and with gigantic formation of program, processing load of computer is increased.

Further, in order to represent behavior of change in the shape of a physical body by computer graphics animation in a physically satisfying form, the change can be provided by using the Finite Element Method, however, when gigantic FEM program is integrated to CG animation program which is inherently gigantic, the program becomes further gigantic and there poses a problem that it is necessary to take into account shortening of an operation time period of a computer executing the program and a computer graphic designer must learn and utilize the Finite Element Method which requires specialized knowledge.

Further, according to current CG animation,

although motion of a physical body is smooth, deformation of the physical body per se is not taken into consideration and therefore, for example, although a motion per se of a person is smooth, the shape of muscle remains as it is and also in a case moving a vehicle, although the vehicle per se is moved upwardly and downwardly or leftwardly and rightwardly, when the vehicle makes a turn at a curve, force exerted on a tire is not taken into consideration and therefore, in view of picture as a whole, there is unnaturalness in expression.

The present invention has been carried out in view of the above-described conventional situation and it is an object thereof to provide a method of displaying a load propagation displacement of a physical body capable of displaying a state of an object physical body in a simplified manner in which based on load exerted on a physical body, virtual agents are formed in a matrix shape, individual agents are deformed and load is transmitted to other face other than a load face under a predetermined condition.

#### DISCLOSURE OF THE INVENTION

In order to achieve the above-described object, the present invention according to Claim 1 of the present application is a method of displaying a load propagation displacement of a physical body on a rigid physical body which undergoes displacement constraint from a surrounding in a boundary which does not undergo the displacement constraint from a surrounding, the method comprising a



the same as a value of the load from the contiguous material agent in the load direction is transmitted, and in the boundary agent formed in the rigid physical body which undergoes the displacement constraint, with regard to the load from the contiguous material agent, a load having a value the same as a value of the load is transmitted in a direction reverse to a direction of the load to thereby display the load propagation displacement of the physical body.

Further, the present invention according to Claim 2 of the present invention relates to the display method according to Claim 1 and is characterized in that the first through the n-th material agents are formed in a load propagation direction when the transmitted load is larger than a predetermined threshold value.

Further, the present invention according to Claim 3 of the present application is a computer readable record medium recorded with a program for displaying a load propagation displacement of a physical body by a method of displaying a load propagation displacement of a physical body on a rigid physical body which undergoes displacement constraint from a surrounding in a boundary which does not undergo the displacement constraint from a surrounding by a computer screen, the method comprising a first material agent having a shape of a hexahedron or a plane virtually formed in the physical body at a position of a load exerted to an arbitrary position of the physical body, a second material agent having the same shape virtually formed at a



contiguous face other than a face of the first material agent exerted with the load, a third, a fourth,... an n-th material agent virtually formed similarly and successively up to a boundary between the physical body and the boundary which does not undergo the displacement constraint in the physical body and /or the rigid physical body which undergoes the displacement constraint and boundary agents having predetermined shapes virtually formed at a contact face between the physical body and the boundary which does not undergo the displacement constraint and /or the rigid physical body which undergoes the displacement constraint, wherein in the material agents, with regard to a direction of the load, a predetermined load in accordance with a material property thereof is transmitted to an upper face and a lower face of the physical body in the load direction, a predetermined load in accordance with a strain characteristic of the physical body is transmitted to a face orthogonal to the load direction and a load which undergoes the predetermined displacement constraint is transmitted to an upper face in the load direction of other material agent contiguous to the material agent, with regard to the load, in the boundary agent formed in the boundary which does not undergo the displacement constraint, a load having a value the same as a value of the load from the contiguous material agent in the load direction is transmitted, and in the boundary agent formed in the rigid physical body which undergoes the displacement constraint, with regard to the load from the contiguous

material agent, a load having a value the same as a value of the load is transmitted in a direction reverse to a direction of the load to thereby display the load propagation displacement of the physical body.

Further, the present invention according to Claim 4 of the present application relates to the computer readable record medium recorded with the program described in Claim 3 and is characterized in that the first through the n-th material agents are formed in a load propagation direction when the transmitted load is larger than a predetermined threshold value.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig.1 is a constitution view showing agent formation of an object physical body for displaying load propagation displacement of the physical body according to an embodiment of the present invention.

Fig.2 is a conceptual view of operation in a case of exerting predetermined input load to a material agent of a physical body for displaying load propagation displacement of the physical body according to an embodiment of the present invention.

Fig.3 is a conceptual view of operation in the case of exerting predetermined input load to a two-dimensional material agent for displaying load propagation displacement of a physical body according to an embodiment of the present invention.

Fig.4 is a conceptual view of operation by load transmitted in a direction orthogonal to a direction of

input load in the case of exerting predetermined input load to a two-dimensional material agent for displaying load propagation displacement of a physical body according to an embodiment of the present invention.

Fig.5 is a conceptual view of operation by load transmitted to a boundary agent which does not undergo displacement constraint in a direction of input load of a material agent orthogonally thereto in the case of exerting predetermined input load to a two-dimensional material agent for displaying load propagation displacement of a physical body according to an embodiment of the present invention.

Fig.6 is a conceptual view of operation with regard to input load in arranging a boundary agent which undergoes displacement constraint by a bottom portion of a material agent and returns the input load as it is in the case of exerting predetermined input load to a two-dimensional material agent for displaying load propagation displacement of a physical body according to an embodiment of the present invention.

Fig.7 is an explanatory view of an object physical body and a behavior of subjecting the object physical body to agent formation to display by utilizing a computer for displaying movement of a physical body according to an embodiment of the present invention.

Fig.8 is a graph of stress comparison respectively comparing x-direction and y-direction stresses between agents and FEM according to an embodiment of the present

invention.

Fig.9 is an explanatory view for displaying a result of deforming an object physical body by a method of displaying load propagation displacement of a physical body according to an embodiment of the present invention.

Fig.10 is a graph representing ratios of stress values in x-direction and y-direction by a method of displaying load propagation displacement of a physical body ( plane ) ( the agents ) according to an embodiment of the present invention, to stress values in x-direction and y-direction according to conventional FEM analysis.

Fig.11 is a graph comparing displacements of a method of displaying load propagation displacement of a physical body ( plane ) ( the agents ) according to an embodiment of the present invention and conventional FEM analysis.

#### BEST MODE FOR CARRYING OUT THE INVENTION

A detailed explanation will be given as follows in reference to the drawings of an embodiment of a method of displaying load propagation displacement of a physical body according to the present invention, particularly of a state in which when load is exerted to an arbitrary position of an object physical body, by using a concept of a material agent in the physical body formed from the arbitrary position to a boundary of the physical body and a boundary agent formed at a boundary of the physical body, displacement of the physical body is displayed from agents forming procedure and a load propagation procedure.

Fig.1 is an outline constitution view showing that in a physical body 1 according to the embodiment, when load is exerted to an arbitrary position thereof, a first agent is virtually formed at the position, the load is transmitted in the physical body 1 and is transmitted to boundaries of the physical body 1, several agents are formed and at the boundaries of the physical body 1, new agents 3a and 3b are formed and Fig.2 is a view of load propagation operation showing in further details how the load is transmitted among the respective agents.

In Fig.1, notation 1 designates the physical body constituting an object physical body, notation 2 designates a first material agent formed at, for example, an arbitrary load position of an elastic physical body, notation 3a designates an agent formed at a boundary of the physical body 1, which is a boundary agent formed at a boundary which does not undergo displacement constraint from the surrounding and notation 3b designates an agent formed at a boundary of the physical body 1, which is a boundary agent formed in the rigid physical body which undergoes displacement constraint from the surrounding. Further, notation 4 designates a boundary at which the object physical body 1 according to the embodiment is arranged and which does not undergo displacement constraint from the surrounding, for example, air and notation 5 designates a boundary at which the object physical body 1 according to the embodiment undergoes displacement constraint from the surrounding, for example, a rigid physical body.

That is, there is shown how the load exerted to the physical body 1 is transmitted in the physical body 1 and how the load finally displaces ( deforms ) the physical body 1 and according to the embodiment, when the load is exerted to the arbitrary portion of the object 1, a respective agent is formed at the position, the first material agent 2 partitioned in a predetermined virtual three-dimensional physical body is formed, thereafter, up to an n-th agent 2 in an n-th order is formed at a boundary of the physical body 1. Further, an explanation will be given by assuming the boundary agent 3a formed at a boundary in boundaries which do not undergo displacement constraint from the surrounding and the boundary agent 3b formed at a boundary in boundaries which undergo displacement constraint from the surrounding in the state of arranging the physical body 1.

[Premise of forming agent]

Further, with regard to formation and load transmission of respective agents in the following, a description will given here of basically a two-dimensional structure of a square firstly for convenience to facilitate understanding and a description will be given later of a three-dimensional structure constituted by a cube. That is, as an assumption of arrangement, according to the embodiment, a two-dimensional object physical body arranged in predetermined boundaries is assumed and expression of displacement of respective portions of the two-dimensional object physical body will be tried in reference to Fig.3

through Fig.6 when load is applied at a certain position in the two-dimensional object physical body.

[ Operation of material agent (part 1) ]

The material agent 2 is an assumed object having a virtual shape which is assumed to display displacement in correspondence with external force exerted to the object physical body by virtually partitioning inside of the two-dimensional object physical body by a predetermined shape ( for example, 'square' ) and one material agent 2 ( for example, first material agent 2a ) is formed at an arbitrary position of the two-dimensional object physical body.

When the first material agent 2a is formed, a second material agent 2b having a shape the same as that of the material agent 2a is formed at a position at which an upper side of the second material agent 2b is brought into contact with a bottom side ( BOTTOM edge ) 2a<sub>2</sub> of the material agent 2a in a direction the same as that of a direction of exerting input load P<sub>0</sub>.

Further, when the first material agent 2a is formed, at one side ( LEFT edge ) 2a<sub>3</sub> of the first material agent 2a, there is formed a second material agent 2c having a shape the same as that of the first material agent 2a and at other side ( RIGHT edge ) 2a<sub>4</sub> of the material agent 2a, a similar second material agent 2d is formed.

Fig.3 is a conceptual view of load transmission in a vertical direction when predetermined input load is exerted to the material agent 2a and all of following

material agents formed at the respective portions are assumed to carry out following propagation operation.

According to the embodiment, the material agent 2a is constituted by a square and is constituted by a top side ( TOP edge )  $2a_1$  exerted with the input load  $P_0$ , a bottom side ( BOTTOM edge )  $2a_2$  to which load is transmitted in a direction the same as a direction of exerting the input load  $P_0$ , the one side ( LEFT edge )  $2a_3$  and the other side ( RIGHT edge )  $2a_4$ .

When the input load  $P_0$  is exerted from an upper direction to the material agent 2, the first material agent 2a is formed, the load is transmitted directly below the first material agent 2a and the second material agent 2b is formed in the direction of propagation the load.

For example, when a force received by the top side ( TOP edge ) of the first material agent 2a is designated by load  $P_1$ , the load  $P_1$  becomes load  $P_1$  of the input load  $P_0$  multiplied by a predetermined transmission coefficient  $\alpha_1$

(  $P_1 = \alpha_1 P_0$  ) and when a force received by a top side ( TOP edge ) of the second material agent 2b is designated by load  $P_2$ , the load  $P_2$  becomes load  $P_2$  of the load  $P_1$  multiplied by a predetermined transmission coefficient  $\alpha_2$  (  $P_2 = \alpha_2 P_0$  ).

Further, when the input load  $P_0$  is exerted from the upper direction to the material agent 2, there is formed a second material agent 2c other side ( RIGHT edge )  $2c_4$  of which is brought into contact with the one side ( LEFT edge )  $2a_3$  of the first material agent 2a ( in Fig.3, left side of the material agent 2a ), a friction force is produced



between the one side ( LEFT edge )  $2a_3$  of the material agent  $2a$  and the other side ( RIGHT edge )  $2c_4$  of the material agent  $2c$  and load having a direction the same as a direction of propagation the load  $P_0$  is exerted to a top side ( TOP edge )  $2c_1$  of the material agent  $2c$ .

In this case, a force received by the top side ( TOP edge )  $2c_1$  of the material agent  $2c$  becomes load  $P_3$  of the load  $P_0$  multiplied by a predetermined transmission coefficient  $\alpha_3$  ( $P_3 = \alpha_3 P_0$ ), similarly, there is formed a second material agent  $2d$  one side ( LEFT edge ) of which is brought into contact with the other side ( RIGHT edge )  $2a_4$  of the first material agent  $2a$  ( right side of the material agent  $2a$  in Fig.3 ) and a force received by a top side ( TOP edge )  $2d_1$  of the second material agent  $2d$  also becomes load  $P_3$  of the load  $P_0$  multiplied by the predetermined transmission coefficient  $\alpha_3$  ( $P_3 = \alpha_3 P_0$ ).

That is, when the top portion of the object physical body receives the input load  $P_0$ , the object physical body transmits the load  $P_1$  multiplied by the predetermined transmission coefficient  $\alpha_1$  in the direction the same as that of input load  $P_0$  to thereby form the first material agent  $2a$  in the propagation direction. Then, the load  $P_2$  multiplied by the predetermined transmission coefficient  $\alpha_2$  is transmitted to directly below the first material agent  $2a$  and the second material agent  $2b$  is formed in the propagation direction. Further, when the top portion of the second material agent  $2b$  receives the load  $P_1$ , the second material agent  $2b$  transmits load multiplied

by a predetermined transmission coefficient to directly below the second material agent 2b and a successive third material agent ( not illustrated in Fig.3 ) is formed and receives and successively transmits load multiplied by a predetermined transmission coefficient.

Further, the input load  $P_0$  received by the top portion of the first material agent 2a formes the second material agent 2c and the second material agent 2d contiguous to the first material agent 2a constituting the load propagation direction and by the friction force produced between the second material agent 2c and the second material agent 2d, and the first material agent 2a, the top sides of the second material agent 2c and second material agent 2d are applied with the load  $P_3$  of the input load  $P_0$  multiplied by the predetermined transmission coefficient  $\alpha_3$ .

Further, the second agents 2c and 2d transmit load of the load  $P_3$  multiplied by the predetermined transmission coefficient  $\alpha_1$  with the load  $P_3$  as input load and successive material agents formed directly below the second agents 2c and 2d, are successively transmitted with load of the load  $P_3$  multiplied by the predetermined transmission coefficient  $\alpha_2$ .

In this way, with regard to the input load  $P_0$ , there are repeated transmission of load and formation of material agents in areas in the direction of forming load to be transmitted ( direction the same as that of the input load  $P_0$  ) until load transmitted in the direction the same as

that of the input load  $P_0$  is equal to or smaller than a value which is regarded as effective for being transmitted successively, that is, a predetermined threshold value  $\gamma$ .

[ Operation of material agent ( part 2 ) ]

Next, Fig.4 is a conceptual view of operation by load transmitted in a direction orthogonal to the input direction of the input load  $P_0$  when the predetermined input load  $P_0$  is exerted to the material agent 2 and similar to the above-described material agent 2, the first material agent 2a is formed at an arbitrary position of the two-dimensional object physical body.

After forming the first material agent 2a, the first material agent 2a transmits load in a direction orthogonal to the direction of exerting force component  $P_1$  of the input load  $P_0$  (  $P_1 = \alpha_1 P_0$ ,  $\alpha_1$  : transmission coefficient ). This is because when the first material agent 2a is pressed to crush by a load exerted to the first material agent 2a, there is exerted load of spreading the first material agent 2a in the direction orthogonal to the direction of exerting the force component  $P_1$  of the input load  $P_0$ .

Similar to the above-described, the first material agent 2a is constituted by a square and is constituted by the top side ( TOP edge )  $2a_1$  exerted with the input load  $P_0$ , the bottom side ( BOTTOM edge )  $2a_2$  propagation load in the direction the same as the direction of exerting the force component  $P_1$  of the input load  $P_0$ , the one side ( LEFT edge )  $2a_3$  propagation load in the direction

orthogonal to the direction of exerting the force component  $P_1$  of the input load  $P_0$  and the other side ( RIGHT edge )  $2a_4$ , propagation load in the direction orthogonal to the direction of exerting the force component  $P_1$  of the input load  $P_0$ , when load is transmitted to the one side ( LEFT edge )  $2a_3$  of the first material agent  $2a$ , there is formed the second material agent  $2c$  having the shape the same as that of the first material agent  $2a$  and when load is transmitted to the other side ( RIGHT edge )  $2a_4$  of the first material agent, similarly, the second material agent  $2d$  is formed.

In reference to Fig.4, in the first material agent  $2a$ , when the input load  $P_0$  is received, a face opposed to the load face (  $2a_2$  face in Fig.4 ) is temporarily constrained by the force component  $P_1$ , strain (  $\varepsilon$  ) is produced by Hook's law ( strain of elastic physical body is proportional to stress ), the first material agent  $2a$  is contracted in the direction the same as the direction of exerting the force component  $P_1$  of the input load  $P_0$  and is spread based on Poissons' ratio (  $\nu$  ) in the direction orthogonal to the direction of exerting the force component  $P_1$  of the input load  $P_0$ .

That is, according to the first material agent  $2a$ , when the load in the direction orthogonal to that of the force component  $P_1$  of the input load  $P_0$  is transmitted to the one side ( LEFT edge ), the second material agent  $2c$  is formed in contact with the one side ( LEFT edge )  $2a_3$  of the first material agent  $2a$  and the second material agent

2d is formed in contact with the other side ( RIGHT edge )  
2a<sub>4</sub>.

By forming the second material agent 2c and the second material agent 2d, the material agent 2a which receives the input load  $P_0$  is spread to the one side ( LEFT edge ) 2a<sub>3</sub> and the other side ( RIGHT edge ) 2a<sub>4</sub> by an amount of strain ( $\varepsilon_x = -\beta \cdot \nu \cdot \varepsilon_y$  ( $\beta$ : transmission coefficient ) ).

Then, the side of the other side ( RIGHT edge ) of the second material agent 2c receives load  $P_4$  ( $P_4 = (1 - \beta) \cdot \nu \cdot \varepsilon_y \cdot A_3 \cdot E$  ( $A_3$ : sectional area of 2a<sub>3</sub> face,  $E$ : Young's modulus of material ) ) and the side of the one side ( LEFT edge ) of the second material agent 2d receives load  $P_4$  ( $P_4 = (1 - \beta) \cdot \nu \cdot \varepsilon_y \cdot A_4 \cdot E$ ) having an amount same as that of the load  $P_4$  which the second material agent 2c receives in a direction reverse thereto.

Further, with regard to the input load  $P_0$ , there are repeated transmission of load until load transmitted orthogonally to the input load  $P_0$  becomes equal to or smaller than the predetermined threshold value  $\gamma$  and formation and load transmission of material agents in areas in the direction of forming the load ( the vertical direction ).

[ Operation of boundary agent which does not undergo displacement constraint ]

Fig.5 schematically shows, in the case in which predetermined input load is exerted to the material agent 2, for example, when the physical body 1 is disposed in a

boundary which does not undergo displacement constraint from the surrounding, what influence is effected from the boundary to the physical body 1 and is a conceptual view of operation in which when the side  $2a_4$  of the second material agent 2 formed at a boundary of the physical body 1 is brought into contact with, for example, air 4, with regard to the input load by the side ( RIGHT edge ), there is shown what load is transmitted in the boundary agent 3a, to thereby show an amount and a direction of the load.

In Fig.5, when load in a direction orthogonal to the side ( RIGHT edge )  $2a_4$  of the material agent 2 is applied, the boundary agent 3a is formed in contact with the side ( RIGHT edge )  $2a_4$  of the material agent 2 and load  $P_s$  exerted from the side ( RIGHT edge )  $2a_4$  of the material agent 2 is returned to the material agent 2a by the boundary agent 3a as load  $P_s'$  having the same magnitude and same direction.

In this case, when the load transmitted to the material agent  $2a_4$  is equal to or smaller than the threshold value, the boundary agent 3a is not formed and the load is not transmitted.

[ Operation of boundary agent which undergoes displacement constraint ]

Fig.6 is a conceptual view of operation in which in the case of exerting predetermined input load to the material agent 2, for example, when the material agent 2a is brought into contact with the rigid physical body 5, in

the boundary agent 3b formed there, there is shown what load is transmitted in correspondence with the input load, to thereby show an amount and a direction of the load.

In Fig.6, when load  $P_e$  having the direction the same as that of the input load  $P_0$  is transmitted from the bottom side ( BOTTOM edge )  $2a_2$  of the material agent 2a which receives the input load  $P_0$  ( not illustrated in Fig.6 ), the rigid physical body 5 is formed with the boundary agent 3b in the square shape according to the embodiment similar to the material agent 2. Further, in correspondence with load  $P_e$  transmitted from above ( TOP edge ) of the boundary agent 3b, load  $P_e'$  having an amount the same as that of the load  $P_e$  is returned from the boundary agent 3b to the material agent 2a. This is because the position of forming the boundary agent 3b is disposed in the rigid physical body 5 and strain is not produced by the load received from the material agent 2a. Further, similar to the above-described, when the load transmitted to the material agent  $2a_2$  is equal to or smaller than the predetermined threshold value  $\gamma$ , the boundary agent 3b is not formed and the load is transmitted.

In this way, according to the material agent 2 successively formed in the direction the same as the direction of exerting the input load  $P_0$  or the direction orthogonal to that of the input load  $P_0$ , load transmitted from the material agent 2 declines based on the predetermined conduction factor. For example, assuming an elastic physical body such as rubber, when predetermined

input load is exerted to a portion of a top face of the rubber ( elastic physical body ), a position thereof exerted with the input load is significantly recessed ( warped ), the more remote the distance from the input load position, the smaller the recess ( warp ), when the rubber ( elastic physical body ) formed with material agent is mounted on a rigid physical body ( boundary agent 3 ) such as, for example, a concrete base, load transmitted from the rubber ( elastic physical body ) is exerted to the concrete base ( rigid physical body ) and the load amount is returned to the rubber ( elastic physical body ) and strain is not produced at all in the concrete face ( rigid physical body ).

Next, with regard to a method of displaying movements of the respective agents of the above-described two-dimensional object physical body, an explanation will be given of a behavior of actually calculating by a computer and displaying on a screen, movement of the two-dimensional object physical body.

Incidentally, a computer used in the embodiment is a personal computer having a memory of 128 Mbyte and mounted with CPU of Celeron 400MHz made by intel Co. and as software, JAVA language ( Ver.1.1.7 ) with Swing 1.1 made by SunMicrosystems Co. and VisualCafe Ver 3.0c made by Symantec Co. are used.

Fig.7 is an explanatory view of a behavior of subjecting a two-dimensional object physical body to agent formation and displaying load propagation displacement of



input load is exerted to a portion of a top face of the rubber ( elastic physical body ), a position thereof exerted with the input load is significantly recessed ( warped ), the more remote the distance from the input load position, the smaller the recess ( warp ), when the rubber ( elastic physical body ) formed with material agent is mounted on a rigid physical body ( boundary agent 3 ) such as, for example, a concrete base, load transmitted from the rubber ( elastic physical body ) is exerted to the concrete base ( rigid physical body ) and the load amount is returned to the rubber ( elastic physical body ) and strain is not produced at all in the concrete face ( rigid physical body ).

Next, with regard to a method of displaying movements of the respective agents of the above-described two-dimensional object physical body, an explanation will be given of a behavior of actually calculating by a computer and displaying on a screen, movement of the two-dimensional object physical body.

Incidentally, a computer used in the embodiment is a personal computer having a memory of 128 Mbyte and mounted with CPU of Celeron 400MHz made by intel Co. and as software, JAVA language ( Ver.1.1.7 ) with Swing 1.1 made by SunMicrosystems Co. and VisualCafe Ver 3.0c made by Symantec Co. are used.

Fig.7 is an explanatory view of a behavior of subjecting a two-dimensional object physical body to agent formation and displaying load propagation displacement of

the physical body by utilizing the computer.

In this case, with regard to a method of displaying load propagation displacement of a physical body according to the invention, a program of a display method may previously be recorded to a computer readable record medium and the program may be read from the record medium.

First, as information of a virtual object physical body, there are given to the computer, a flat plate constituted by sizes of a width of 200mm, a height of 200mm and a thickness of 2mm, as conditions of material agents, Young's modulus of 206 Gpa, Poissons' ratio 0.3, input load from upper direction of 2N, as conduction factor of material agents, there are previously given  $\alpha_1 = 0.5$ ,  $\alpha_2 = 0.25$ ,  $\alpha_3 = 0.25$  and  $\beta = 0.5$  further, there is given the threshold value  $\gamma = 10E-3$ .

When the above-described conditions of the object physical body ( material agents ) are inputted to the computer and the input load ( for example, the above-described load of 2N ) is given to an arbitrary position of the object physical body from above in a lower direction, the material agent 2 is formed when the transmitted load is larger than the threshold value  $\gamma$  and deformation and load transmission of the material agent 2 are carried out.

When the calculation of deformation and transmitted load has been finished until the transmitted load becomes smaller than the predetermined threshold value  $\delta$  for all of formed agents, the result is displayed to, for example, a display apparatus, a printer or the like connected to the

computer and motion of the two-dimensional object physical body is displayed.

Further, although the conditions of the object physical body ( material agents ) may be inputted for each object physical body, conditions of a plurality of object physical bodies may previously be inputted, formed into a data base and stored.

Fig.8 is a graph representing ratios of stress values in x-direction and y-direction by a method of displaying motion of the physical body ( plane ) according to the present invention ( the agents ), to stress values in x-direction and y-direction by conventional FEM analysis, further, Fig.9 is a graph of stress comparison for respectively comparing stresses in x-direction and y-direction between the above-described agent and FEM and in either of the graphs, tendencies are substantially coincident, particularly, with regard to x-direction of the stress comparison graph ( refer to Fig.9 ), the tendencies are substantially coincident.

Fig.10 illustrates explanatory views displaying the result of deforming the object physical body, Fig.10 ( a ) shows a result calculated by conventional FEM when input load is given to the object physical body and Fig.10 ( b ) represents deformations ( strains ) of respective agents when the input load is given to the object physical body and outline tendencies are indicated in substantially the same mode.

In this case, according to the display method of

the present application, with regard to portions at which external force is not operated to the object physical body, agent formation and load transmission are not carried out and initial states are displayed as they are.

Further, Fig.11 is a graph comparing displacements of the method of displaying the motion of the physical body ( plane ) according to the present invention ( the agents ) and conventional FEM analysis and also according to the graph, tendencies of both remain the same.

In this way, when represented by a matrix having a size the same as that of conventional FEM, although there is a roughness, the calculation is simple and fast and therefore, by subjecting the object physical body to small agent formation and adjusting the conduction factor, substantially similar to display by FEM, the tendency of the displacement of the physical body can sufficiently be displayed.

Further, when with regard to the above-described agents, the input load is repeatedly displayed by, for example, 0.1 N increment up to 2 N, movement of a procedure of deforming the object physical body can be displayed.

Although until here, an explanation has been given two-dimensionally of the material agent 2 and the boundary agent 3, next, as a second embodiment, an explanation will be given three-dimensionally of the material agent 2 and the boundary agent 3 as a method of displaying motion of the physical body according to the present invention.

Fig.2, mentioned above, is a load propagation

operation view of a three-dimensional object physical body ( agent ) according to the embodiment and notation 12 assumes a material agent and notation 13 assumes a boundary agent.

For example, when the input load  $P_0$  is exerted to a predetermined position of the material agent 12, according to the embodiment, for example, a material agent 12a of a cube is formed, when the material agent 12a is formed, based on the predetermined transmission coefficient  $\alpha_1$ , the load  $P_1$  in the direction the same as that of the input load  $P_0$  is transmitted, successively, at a bottom face of the material agent 12a in the direction the same as at of the input load  $P_1$ , successively, at a bottom face of the material agent 12a disposed in a direction the same as that of the input load  $P_1$ , based on the predetermined transmission coefficient  $\alpha_2$ , the load  $P_2$  in the direction the same as that of the input load  $P_0$  is transmitted, there is formed a material agent 12b having a shape the same as that of the material agent 12a, an upper face of which is brought into contact with an area in the propagation direction ( bottom face of material agent 12a ) and material agents 12 are successively formed and load is transmitted in the direction the same as that of the input load  $P_0$  until the load becomes equal to or smaller than the predetermined threshold value  $\gamma$  or a material agent 12h is reached.

Further, when the material agent 12a is formed, in a direction the same as the direction of exerting the input

load  $P_0$ , that is, at four side faces of the material agent 12a, friction forces are exerted, similar to the above-described first embodiment, based on the predetermined transmission coefficient  $\alpha$ , the load  $P_1$  in the direction the same as that of the input load  $P_0$  is transmitted and there are respectively formed material agents 12c, 12d, 12e and 12f having a shape the same as that of the material agent 12a.

That is, in Fig.2, at a front side face on the right side of the material agent 12a, the material agent 12c is formed, at a front side face on the left side of the material agent 12a, the material agent 12d is formed, at a rear side face on the LEFT edge side, the material agent 12e is formed and at a rear side face on the right side, the material agent 12f is formed, respectively.

Further, similar to the above-described formation of agents and load transmission, the material agent 12a is pressed to crush by receiving the force component  $P_1$  of the input load  $P_0$  and is spread in the horizontal direction by the amount of strain and load  $P_4$  ( $P_4 = (1 - \beta) \cdot \nu \cdot \epsilon_y \cdot A \cdot E$  (A: sectional area of a side face of the material agent 2a, E: Young's ratio of material)) is transmitted in directions vertical to the respective side faces (four directions according to embodiment) (directions orthogonal to the input load  $P_0$ ).

Further, when loads  $P_n$  are transmitted to the respective material agents 12c, 12d, 12e, 12f..., material agents 12 are formed and load is transmitted until load

becomes the predetermined threshold value  $\nu$  or material agents 12g are reached, successively, similarly, material agents ( not illustrated in Fig.2 ) are formed in contact with side faces of the material agent 12b and load is transmitted.

Further, similar to the above-described, when a side face of the material agent 12g is a boundary which is not subjected to displacement constraint ( for example, in air ), the boundary agent 13a is formed and load  $P_s$  exerted from one side face thereof to be returned to the material agent 12g, is exerted to the boundary agent 13a as load  $P_s'$  as it is.

Further, when load  $P_e$  in the direction the same as that of the input load  $P_0$  is transmitted from a bottom face of the material agent 12h propagation load by receiving the force component  $P_1$  of the input load  $P_0$ , there is formed a boundary agent 13b of a cube at a boundary subjected to displacement constraint ( for example, rigid physical body ) and with regard to the load  $P_e$  transmitted from the upper face of the boundary agent 13b, load  $P_e'$  having an amount the same as that of the load  $P_e$  is returned from the boundary agent 13b to the material agent 12h.

In this way, also with regard to the three-dimensional physical body, similar to the above-described two-dimensional structure object physical body, the respective agents are formed and load is transmitted and behavior of displacement can easily be calculated.

Further, although according to the above-described

embodiments, an explanation has been given such that the shape of the respective agent is a square or a cube, the shape may be a regular polygon or a regular polyhedron ( for example, regular hexagon, regular hexahedron ) and the shape is not particularly limited so far as agents having the same shape are formed contiguously with no gap therebetween.

Further, although according to the above-described embodiments, an explanation has been given such that a boundary agent which does not undergo displacement constraint is air, the boundary agent may be water ( liquid ), vacuum or gasses of specified kinds and composition of the boundary agent is not particularly limited.

Further, although according to the above-described embodiments, an explanation has been given such that a boundary agent which undergoes displacement constraint is a rigid physical body, other than the rigid physical body, the boundary agent may be other physical body having a transmission coefficient and in that case, operation ( having different transmission coefficient ) may be carried out by a method similar to that of the above-described material agent.

#### INDUSTRIAL APPLICABILITY

According to the method of displaying load propagation displacement of a physical body of the present invention, with regard to load to an object physical body, a first one of agents is formed, load is transmitted while forming agents successively from the agent based on



predetermined conduction factor and accordingly, the method is easily applicable to displacement analysis of a physical body in the field of physics, particularly, strength of materials, further, in the field of computer graphics, the method can be integrated to an application program such as game or the like and formation of computer graphics animation can simply be realized when a displayed deformed state of a physical body is displayed. Thereby, there is no need of learning and utilizing the finite element method requiring specialized knowledge, further, the program is simplified and therefore, there is achieved an advantage of capable of achieving to shorten an operation time period ( time period required for displaying displacement of physical body ) of a computer executing thereof.

Further, according to the method of displaying load propagation displacement of a physical body of the invention, with regard to portions which do not receive load ( equal to or lower than predetermined threshold value ) there is no need of carrying out formation of agents and transmission of load and accordingly, whereas conventionally, in displaying partial displacement of a physical body, a state of a total is to operate, there is no need of carrying out operation with regard to portions having no displacement and therefore, there are achieved extremely excellent characteristic and effect of capable of significantly shortening the operation time period of a computer which is required for displaying the total.

In this way, specialized knowledge is dispensed

with and processing load of a computer can be alleviated and accordingly, the present invention can be utilized for a computer game by computer graphics, background ( frame ) of movie or the like, the present invention is applicable to analyzing a stress state of a machine or a structure and its simulation, further, the present invention can widely be utilized not only in physical properties but also in calculation and simulation display of tendency of displacement in a fluid and so on.

Further, by combining the display method for displaying load propagation displacement of a physical body according to the present invention with CG animation software, the display can be carried out in consideration of deformation of the physical body per se and accordingly, for example, tendency and shape of the muscle of a person can be displayed or when vehicle makes a turn at a curve, in consideration of force exerted to a tire, natural movement can be expressed similar to real picture ( photographing by a video camera or the like ).

CLAIM(S)

1. A calculation method for physical body deformation under load propagation which is a method of displaying a load propagation displacement of a physical body on a rigid physical body which undergoes displacement constraint from a surrounding in a boundary which does not undergo the displacement constraint from a surrounding, said method comprising a first material agent having a shape of a hexahedron or a plane virtually formed in the physical body at a position of a load exerted to an arbitrary position of the physical body, a second material agent having the same shape virtually formed at a contiguous face other than a face of the first material agent exerted with the load, a third, a fourth,... an n-th material agent virtually formed similarly and successively up to a boundary between the physical body and the boundary which does not undergo the displacement constraint in the physical body and /or the rigid physical body which undergoes the displacement constraint and boundary agents having predetermined shapes virtually formed at a contact face between the physical body and the boundary which does not undergo the displacement constraint and /or the rigid physical body which undergoes the displacement constraint, wherein in the material agents, with regard to a direction of the load, a predetermined load in accordance with a material property thereof is transmitted to an upper face and a lower face of the physical body in the load direction, a predetermined load in accordance with a strain

characteristic of the physical body is transmitted to a face orthogonal to the load direction and a load which undergoes the predetermined displacement constraint is transmitted to an upper face in the load direction of other material agent

contiguous to the material agent, with regard to the load, in the boundary agent formed in the boundary which does not undergo the displacement constraint, a load having a value the same as a value of the load from the contiguous material agent in the load direction is transmitted, and in the boundary agent formed in the rigid physical body which undergoes the displacement constraint, with regard to the load from the contiguous material agent, a load having a value the same as a value of the load is transmitted in a direction reverse to a direction of the load to thereby display the load propagation displacement of the physical body.

2. The display method according to Claim 1, characterized in that the first through the n-th material agents are formed in a load propagation direction when the transmitted load is larger than a predetermined threshold value.

3. A computer readable record medium recorded with a program for displaying a load propagation displacement of a physical body by a method of displaying a load propagation displacement of a physical body on a rigid physical body which undergoes displacement constraint from a surrounding in a boundary which does not undergo the

displacement constraint from a surrounding by a computer screen, said method comprising a first material agent having a shape of a hexahedron or a plane virtually formed in the physical body at a position of a load exerted to an arbitrary position of the physical body, a second material agent having the same shape virtually formed at a contiguous face other than a face of the first material agent exerted with the load, a third, a fourth,... an n-th material agent virtually formed similarly and successively up to a boundary between the physical body and the boundary which does not undergo the displacement constraint in the physical body and /or the rigid physical body which undergoes the displacement constraint and boundary agents having predetermined shapes virtually formed at a contact face between the physical body and the boundary which does not undergo the displacement constraint and /or the rigid physical body which undergoes the displacement constraint, wherein in the material agents, with regard to a direction of the load, a predetermined load in accordance with a material property thereof is transmitted to an upper face and a lower face of the physical body in the load direction, a predetermined load in accordance with a strain characteristic of the physical body is transmitted to a face orthogonal to the load direction and a load which undergoes the predetermined displacement constraint is transmitted to an upper face in the load direction of other material agent contiguous to the material agent, with regard to the load, in the boundary agent formed in the

boundary which does not undergo the displacement constraint, a load having a value the same as a value of the load from the contiguous material agent in the load direction is transmitted, and in the boundary agent formed in the rigid physical body which undergoes the displacement constraint, with regard to the load from the contiguous material agent, a load having a value the same as a value the load is transmitted in a direction reverse to a direction of the load to thereby display the load propagation displacement of the physical body.

4. The computer readable record medium recorded with the program according to Claim 3, characterized in that the first through the n-th material agents are formed in a load propagation direction when the transmitted load is larger than a predetermined threshold value.

## ABSTRACT


According to a method of displaying a load propagation displacement of a physical body of the present invention, a first material agent 2a is formed in a shape of a hexahedron or a plane virtually formed in the physical body at a load face position given to an arbitrary position of the physical body 1, a second material agent 2b is formed in the same shape virtually formed at a contiguous face of the first material agent 2a other than a face receiving the load and a third, a fourth...and an n-th material agent 2 are virtually formed in the physical body up to a boundary between the physical body and the boundary, boundary agents 3a and 3b are constituted by predetermined shapes virtually formed at a contact boundary between the physical body and the boundary which undergo and /or do not undergo displacement constraint from a surrounding, in the material agents 2, with regard to a load direction, a predetermined load in accordance with a material property thereof is transmitted to an upper face and a lower face of the physical body in the load direction, a predetermined load in accordance with a strain property of the physical body is transmitted to a face orthogonal to the load direction and a load which undergoes predetermined displacement constraint is transmitted to an upper face in the load direction of other material agent 2 contiguous to the material agent 2 and at the boundary agent 3, with regard to load from the contiguous material agent 2, a load having the same value in the load direction

is transmitted to the boundary which does not undergo the displacement constraint and a load having a value the same as a value of the load is transmitted in a direction reverse to a direction of the load from the contiguous material agent at the boundary which undergoes the displacement constraint to thereby display the load propagation displacement of the physical body in contact with the boundary.

According to the method of displaying the load propagation displacement of the physical body of the present invention, with regard to a load to the object physical body, the first one of the agents is formed and the load is transmitted while successively forming agents from the agent based on predetermined conduction factor and accordingly, the method is easily applicable to displacement analysis of a physical body in the field of physics, particularly strength of materials and further, in the field of computer graphics, the method is integrated to an application program of a game or the like and formation of computer graphics animation in displaying a deformed state of a displayed object can simply be realized.




Fig. 1



09856179-000001

Fig. 2



09856179-080601

1. *Chlorophyll a* (Chl *a*)  
 2. *Chlorophyll b* (Chl *b*)  
 3. *Carotenoids*  
 4. *Phycocyanin*  
 5. *Peridinin*  
 6. *Algae*  
 7. *Phaeophytin*  
 8. *Phaeopigments*  
 9. *Phaeoerythrin*  
 10. *Phaeoalcohol*  
 11. *Phaeoaldehyde*  
 12. *Phaeoaldehyde*  
 13. *Phaeoaldehyde*  
 14. *Phaeoaldehyde*  
 15. *Phaeoaldehyde*  
 16. *Phaeoaldehyde*  
 17. *Phaeoaldehyde*  
 18. *Phaeoaldehyde*  
 19. *Phaeoaldehyde*  
 20. *Phaeoaldehyde*  
 21. *Phaeoaldehyde*  
 22. *Phaeoaldehyde*  
 23. *Phaeoaldehyde*  
 24. *Phaeoaldehyde*  
 25. *Phaeoaldehyde*  
 26. *Phaeoaldehyde*  
 27. *Phaeoaldehyde*  
 28. *Phaeoaldehyde*  
 29. *Phaeoaldehyde*  
 30. *Phaeoaldehyde*  
 31. *Phaeoaldehyde*  
 32. *Phaeoaldehyde*  
 33. *Phaeoaldehyde*  
 34. *Phaeoaldehyde*  
 35. *Phaeoaldehyde*  
 36. *Phaeoaldehyde*  
 37. *Phaeoaldehyde*  
 38. *Phaeoaldehyde*  
 39. *Phaeoaldehyde*  
 40. *Phaeoaldehyde*  
 41. *Phaeoaldehyde*  
 42. *Phaeoaldehyde*  
 43. *Phaeoaldehyde*  
 44. *Phaeoaldehyde*  
 45. *Phaeoaldehyde*  
 46. *Phaeoaldehyde*  
 47. *Phaeoaldehyde*  
 48. *Phaeoaldehyde*  
 49. *Phaeoaldehyde*  
 50. *Phaeoaldehyde*  
 51. *Phaeoaldehyde*  
 52. *Phaeoaldehyde*  
 53. *Phaeoaldehyde*  
 54. *Phaeoaldehyde*  
 55. *Phaeoaldehyde*  
 56. *Phaeoaldehyde*  
 57. *Phaeoaldehyde*  
 58. *Phaeoaldehyde*  
 59. *Phaeoaldehyde*  
 60. *Phaeoaldehyde*  
 61. *Phaeoaldehyde*  
 62. *Phaeoaldehyde*  
 63. *Phaeoaldehyde*  
 64. *Phaeoaldehyde*  
 65. *Phaeoaldehyde*  
 66. *Phaeoaldehyde*  
 67. *Phaeoaldehyde*  
 68. *Phaeoaldehyde*  
 69. *Phaeoaldehyde*  
 70. *Phaeoaldehyde*  
 71. *Phaeoaldehyde*  
 72. *Phaeoaldehyde*  
 73. *Phaeoaldehyde*  
 74. *Phaeoaldehyde*  
 75. *Phaeoaldehyde*  
 76. *Phaeoaldehyde*  
 77. *Phaeoaldehyde*  
 78. *Phaeoaldehyde*  
 79. *Phaeoaldehyde*  
 80. *Phaeoaldehyde*  
 81. *Phaeoaldehyde*  
 82. *Phaeoaldehyde*  
 83. *Phaeoaldehyde*  
 84. *Phaeoaldehyde*  
 85. *Phaeoaldehyde*  
 86. *Phaeoaldehyde*  
 87. *Phaeoaldehyde*  
 88. *Phaeoaldehyde*  
 89. *Phaeoaldehyde*  
 90. *Phaeoaldehyde*  
 91. *Phaeoaldehyde*  
 92. *Phaeoaldehyde*  
 93. *Phaeoaldehyde*  
 94. *Phaeoaldehyde*  
 95. *Phaeoaldehyde*  
 96. *Phaeoaldehyde*  
 97. *Phaeoaldehyde*  
 98. *Phaeoaldehyde*  
 99. *Phaeoaldehyde*  
 100. *Phaeoaldehyde*






Fig. 4



09856179-080601

Fig.5



09856179.000001

Fig. 6






Fig. 7



09856179-080601

Fig. 8



109080-62132860



Fig. 9





Fig. 10




(a)

20	21		23	24
15	18		18	19
13	11	2	13	14
5	6	7	3	9
0	1	2	3	4

(b)

09856179-080601

Fig.11



## Declaration and Power of Attorney For Patent Application

## 特許出願宣言書及び委任状

## Japanese Language Declaration

## 日本語宣言書

下記の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者（下記の名称が複数の場合）であると信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled.

CALCULATION METHOD FOR PHYSICAL

BODY DEFORMATION UNDER LOAD

PROPAGATION

上記発明の明細書は、

the specification of which

本書に添付されています。

☐ is attached hereto.

\_\_\_\_月\_\_\_\_日に提出され、米国出願番号または特許協定条約国際出願番号を\_\_\_\_とし、  
(該当する場合) \_\_\_\_\_に訂正されました。

☒ was filed on 19 July 2000

as United States Application Number or

PCT International Application Number

PCT/JP00/04834

and was amended on

\_\_\_\_ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1条56項に定義されるとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

# Japanese Language Declaration

(日本語宣言書)

私は、米国法典第35編119条 (a) - (d) 項又は365条 (b) 項に基づき下記の、米国以外の国の少なくとも一カ国を指定している特許協力条約365 (a) 項に基づく国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

Prior Foreign Application(s)

外国での先行出願

2000-3496

Japan

(Number)  
(番号)

(Country)  
(国名)

(Number)  
(番号)

(Country)  
(国名)

I hereby claim foreign priority under Title 35, United States Code, Section 119 (a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or Section 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Priority Claimed

優先権主張

☒ Yes  
はい

☐ No  
いいえ

12/01/00

(Day/Month/Year Filed)  
(出願年月日)

(Day/Month/Year Filed)  
(出願年月日)

☐ Yes  
はい

☐ No  
いいえ

私は、第35編米国法典119条 (e) 項に基づいて下記の米国特許出願規定に記載された権利をここに主張いたします。

(Application No.)  
(出願番号)

(Filing Date)  
(出願日)

私は、下記の米国法典第35編120条に基づいて下記の米国特許出願に記載された権利、又は米国を指定している特許協力条約365条 (c) 項に基づく権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米国特許出願に開示されていない限り、その先行米国出願書提出日以降で本出願書の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

PCT/JP00/04834

July 19, 2000

(Application No.)  
(出願番号)

(Filing Date)  
(出願日)

(Application No.)  
(出願番号)

(Filing Date)  
(出願日)

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

(Application No.)  
(出願番号)

(Filing Date)  
(出願日)

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or Section 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of application.

(Status: Patented, Pending, Abandoned)  
(現況：特許許可済、係属中、放棄済)

(Status: Patented, Pending, Abandoned)  
(現況：特許許可済、係属中、放棄済)

私は、私自信の知識に基づいて本宣言書中で私が行なう表明が真実であり、かつ私の入手した情報と私の信じることに基づく表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の声明を行なえば、出願した、又は既に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

**Japanese Language Declaration**  
(日本語宣言書)

委任状：私は下記の発明者として、本出願に関する一切の手続きを米特許商標局に対して遂行する弁理士または代理人として、下記の者を指名いたします。  
(弁理士、または代理人の指名及び登録番号を明記のこと)

**POWER OF ATTORNEY:** As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith: (list name and registration number)

Norman F. Oblon, Reg. No. 24,618; Marvin J. Spivak, Reg. No. 24,913; C. Irvin McClelland, Reg. No. 21,124; Gregory J. Maier, Reg. No. 25,599; Arthur I. Neustadt, Reg. No. 24,854; Richard D. Kelly, Reg. No. 27,757; James D. Hamilton, Reg. No. 28,421; Eckhard H. Kuesters, Reg. No. 28,870; Robert T. Pous, Reg. No. 29,099; Charles L. Gholz, Reg. No. 26,395; William E. Beaumont, Reg. No. 30,996; Jean-Paul Lavalleye, Reg. No. 31,451; Stephen G. Baxter, Reg. No. 32,884; Richard L. Treanor, Reg. No. 36,379; Steven P. Weihrouch, Reg. No. 32,829; John T. Goolkasian, Reg. No. 26,142; Richard L. Chinn, Reg. No. 34,305; Steven E. Lipman, Reg. No. 30,011; Carl E. Schlier, Reg. No. 34,426; James J. Kulbaski, Reg. No. 34,648; Richard A. Neifeld, Reg. No. 35,299; J. Derek Mason, Reg. No. 35,270; Surinder Sachar, Reg. No. 34,423; Jeffrey B. McIntyre, Reg. No. 36,867; William T. Enos, Reg. No. 33,128; Michael E. McCabe, Jr., Reg. No. 37,182; Bradley D. Lytle, Reg. No. 40,073; and Michael R. Casey, Reg. No. 40,294, with full powers of substitution and revocation.

書類送付先

Send Correspondence to:

OBLON, SPIVAK, MCCLELLAND, MAIER & NEUSTADT, P.C.  
FOURTH FLOOR  
1755 JEFFERSON DAVIS HIGHWAY  
ARLINGTON, VIRGINIA 22202 U.S.A.

直接電話連絡先: (名前及び電話番号)

Direct Telephone Calls to: (name and telephone number)

(703) 413-3000

単独発明者または第一の共同発明者の氏名 1-00		Full name of sole or first joint inventor <u>Yasukazu NISHI</u>	
発明者の署名	日付	Inventor's signature <u>Y. Nishi</u>	Date <u>Jul 20, 2001</u>
住所	Residence 6-10-1202, Toyosu 5-chome, Koto-ku, Tokyo JP		
国籍	Citizenship Japan 135-0061 Japan		
郵便の宛先	Post Office Address Same as Above		
第二の共同発明者の氏名		Full name of second joint inventor, if any	
第二の共同発明者の署名	日付	Second joint Inventor's signature	Date
住所	Residence		
国籍	Citizenship		
郵便の宛先	Post Office Address		

(第三以降の共同発明者についても同様に記載し、署名すること)

(Supply similar information and signature for third and subsequent joint inventors.)